

Features


- Revolutionary semiconductor material - Silicon Carbide
- Benchmark switching behavior
- No reverse recovery/ No forward recovery
- Temperature independent switching behavior
- Optimized for high temperature operation
- Qualified according to JEDEC criteria

Applications

- Switch mode power supply
- Power factor correction
- Solar inverter
- Uninterruptible power supply

Description

- System efficiency improvement over Si diodes
- Enabling higher frequency / increased power density solutions
- System size/cost savings due to reduced heatsink requirements and smaller magnetics
- Reduced EMI
- Highest efficiency across the entire load range
- Robust diode operation during surge events
- High reliability



Key performance parameters

Product Summary

V_{DC}	650V
I_F	10A
$T_{j,max}$	175°C

Package Marking and Ordering Information

Part #	Marking	Package	Packing	Reel Size	Tape Width	Qty
PESC1065GG	PESC1065GG	TO-252-2L	Tape&Reel	13 inches	16mm	2500pcs

Absolute Maximum Ratings

Parameter	Symbol	Value	Unit
Repetitive peak reverse voltage	V_{RRM}	650	V
Continuous forward current for $T_C = 150^\circ\text{C}$	I_F	10	A
Non-Repetitive Peak Forward Surge Current $T_C=25^\circ\text{C}, t_p=8.3\text{ ms}$, Half Sine Pulse $T_C=150^\circ\text{C}, t_p=8.3\text{ ms}$, Half Sine Pulse	I_{FSM}	90 80	A
i^2t value $T_C = 25^\circ\text{C}$, $t_p=8.3\text{ ms}$ i^2t value $T_C = 150^\circ\text{C}$, $t_p=8.3\text{ ms}$	$\int i^2 dt$	34 27	A^2s
Total power dissipation $T_C = 25^\circ\text{C}$	P_D	67	W
Operating junction and storage temperature	T_j, T_{stg}	-55 to +175	$^\circ\text{C}$

Thermal Resistance

Parameter	Symbol	Condition	Value			Unit
			min.	typ.	max.	
Thermal resistance, junction – case.	R_{thJC}		-	1.5	2.2	°C/W
Thermal resistance, junction - ambient(min. footprint)	R_{thJA}		-	-	50	°C/W

Electrical Characteristic

Static Characteristic ($T_j=25^{\circ}\text{C}$ unless otherwise noted)

Parameter	Symbol	Test Condition	Value			Unit
			min.	typ.	max.	
DC blocking voltage	V_{DC}	$I_R=100\mu\text{A}$	650	-	-	V
Forward voltage	V_F	$I_F=10\text{A}, T_j=25^{\circ}\text{C}$	-	1.4	1.7	V
		$I_F=10\text{A}, T_j=150^{\circ}\text{C}$	-	1.77	2.0	V
Reverse current	I_R	$V_R=650\text{V}, T_j=25^{\circ}\text{C}$		0.1	10	μA
		$V_R=650\text{V}, T_j=150^{\circ}\text{C}$	-	2	100	

Dynamic Characteristic ($T_j=25^{\circ}\text{C}$ unless otherwise noted)

Parameter	Symbol	Test Condition	Value			Unit
			min.	typ.	max.	
Total capacitance	C	$V_R=0.1\text{V}, f=1\text{MHz}$	-	475	-	pF
		$V_R=200\text{V}, f=1\text{MHz}$	-	49	-	
		$V_R=400\text{V}, f=1\text{MHz}$	-	48	-	
Total capacitive charge	Q_C	$V_R=400\text{V}, Q_c=\int_0^{V_R} C(V)dV$	-	27	-	nC

Typical Performance Characteristics

Fig 1: Forward Characteristics




Fig 2: Reverse Characteristics




Fig 3: Total Capacitance Charge VS. Reverse Voltage




Fig 4: Capacitance Characteristics




Fig 5: Power Dissipation






Fig 6: Max. Transient Thermal Impedance





Package Outline: TO-252-2L



SYMBOL	MILLIMETERS		INCHES	
	MIN	MAX	MIN	MAX
A	2.15	2.45	0.085	0.096
A1	0.05	0.20	0.002	0.008
A2	0.91	1.22	0.036	0.048
B	0.66	0.86	0.026	0.034
B1	0.93	1.23	0.037	0.048
C	0.40	0.60	0.016	0.024
C1	0.40	0.60	0.016	0.024
D	5.95	6.25	0.234	0.246
D1	4.80		0.189	
D2	3.80		0.150	
E	6.45	6.75	0.254	0.266
E1	5.12	5.52	0.202	0.217
L	1.65		0.065	
L1	1.58	1.98	0.062	0.078
L2	0.60	1.00	0.024	0.039
L3	0.70	1.00	0.028	0.039
L4	0.00	0.20	0.000	0.008
L5	2.80	3.40	0.110	0.134
H	9.80	10.40	0.386	0.409
θ	0.00	8.00	0.000	0.315
e	4.57		0.180	

Disclaimer

Any and all semiconductor products have certain probability to fail or malfunction, which may result in personal injury, death or property damage. Customer are solely responsible for providing adequate safe measures when design their systems.

Unless otherwise specified in the datasheet, the product is designed and qualified as a standard commercial product and is not intended for use in applications that require extraordinary levels of quality and reliability, such as automotive, aviation/aerospace and life-support devices or systems.

Buyer is responsible for its products and applications using PingWei products, including compliance with all laws, regulations and safety requirements or standards, regardless of any support or applications information provided by PingWei.

"Typical" parameters which may be provided in PingWei data sheets and/or specifications can and do vary in different applications and actual performance may vary over time. All operating parameters, including "Typicals" must be validated for each customer application by customer's technical experts

ALL PRODUCT, PRODUCT SPECIFICATIONS AND DATA ARE SUBJECT TO CHANGE WITHOUT NOTICE TO IMPROVE RELIABILITY, FUNCTION OR DESIGN OR OTHERWISE